

Amendments to the Claims

The following listing of the claims will replace all prior versions, and listings, of claims in the application. Inserted material is underlined and deleted material is shown in strikethrough to show the changes made.

1. (Currently Amended) A method for networking a plurality of television recording devices, said method comprising the steps of:

receiving a plurality of television signals;

selecting a set of tuners from a plurality of tuners available on a network;

tuning each of said television signals in one of a the tuners selected from the plurality of tuners;

buffering said television signals on a storage medium in at least one PVR media server, the PVR media server configured for maintaining a write position for the buffering;

coupling a plurality of clients, over a the network, to said PVR media server;

assigning at least two of said clients to one or more of said tuners; and

transferring, over said network, buffered television signals to said clients.

2. (Original) The method as set forth in claim 1, wherein the step of tuning each of said television signals in one of a plurality of tuners comprises the step of tuning said television signals in a plurality of tuners located in a single PVR media server.

3. (Currently Amended) The method as set forth in claim 1, wherein the step of tuning each of

said television signals in one of a plurality of tuners comprises the step of tuning said television signals in a plurality of tuners located in a plurality of PVR media servers.

4. (Original) The method as set forth in claim 1, wherein the step of buffering said television signals on a storage medium comprises the step of storing at least one television signal on a storage medium in at least one PVR media server for a client so as to record at least one television program for said client.

5. (Original) The method as set forth in claim 4, wherein the step of storing at least one television signal comprises the steps of:

assigning a tuner to said client;

allocating space on said storage medium to record said television program; and

storing said television signal on said storage medium during a time scheduled for said television program.

6. (Original) The method as set forth in claim 4, wherein the step of storing at least one television signal comprises the step of resolving any conflicts to assign an available tuner for said television signal.

7. (Original) The method as set forth in claim 6, wherein the step of resolving any conflicts to assign an available tuner for said television program comprises the steps of:

determining whether one of said tuners is available to receive said television signal;
if so, assigning said tuner to receive said television signal;
if not, determining which tuners are potentially available;
querying clients assigned to said tuners potentially available to determine whether said clients desire to cancel recordation of said television program; and
assigning a tuner potentially available to receive said television signal if no clients cancel recordation of said television program.

8. (Original) The method as set forth in claim 1, further comprising the steps of:

generating a first position to identify a location within a selected one of said buffered television signals for a first client; and

generating a second position to identify a location within said selected buffered television signal for a second client, said second position being independent from said first position.

9. (Currently Amended) A system comprising:

a plurality of clients for displaying television signals;
at least one PVR media server coupled to receive a plurality of television signals, said PVR media server comprising:

a plurality of television tuners for tuning each of said television signals, so as to assign at least two of said clients to one or more of said tuners, thereby generating a set of assigned clients;

a storage medium, coupled to said television tuners, for buffering said television signals, the PVR media server configured for maintaining a write position for the buffering; and

a network for coupling said clients to said PVR media server and for transferring said buffered television signals to said assigned clients,

wherein the system is configured for selecting a set of tuners for tuning the received signals,

wherein the selected tuners are coupled to storage media for buffering the signals for the assigned clients.

10. (Original) The system as set forth in claim 9, wherein said at least one PVR media server comprises a single PVR media server comprising a plurality of tuners.

11. (Original) The system as set forth in claim 9, wherein said at least one PVR media server comprises a plurality of tuners located in a plurality of PVR media servers.

12. (Original) The system as set forth in claim 9, wherein said PVR media server further comprising storage medium for storing at least one television signal so as to record said television program.

13. (Original) The system as set forth in claim 12, wherein said system further comprises software for assigning a tuner to said client, for allocating space on said storage medium to record said

television program, and for storing said television signal on said storage medium during a time scheduled for said television program.

14. (Original) The system as set forth in claim 12, wherein said system further comprises software for resolving any conflicts to assign an available tuner for said television signal.

15. (Original) The system as set forth in claim 14, further comprising software for determining whether one of said tuners is available to receive said television signal;

if so, for assigning said tuner to receive said television signal;

if not, for determining which tuners are potentially available, for querying clients assigned to said tuners potentially available to determine whether said clients desire to cancel recordation of said television program, and for assigning a tuner potentially available to receive said television signal if no clients cancel recordation of said television program.

16. (Original) The system as set forth in claim 12, further comprising software for generating a first position to identify a location within a selected one of said buffered television signals for a first client, and for generating a second position to identify a location within said selected buffered television signal for a second client, said second position being independent from said first position.

17. (New) A method of networking video recording devices, the method comprising:

receiving a plurality of signals, thereby generating a set of received signals;

selecting a plurality of tuners located within a network;

tuning the received signals by using the tuners selected within the network;

coupling the tuners to a plurality of storage media;

buffering the received signals by using a first storage medium in at least a first PVR media server thereby generating a set of buffered signals, the first PVR media server configured for maintaining a write position for the buffering.

18. (New) The method of claim 17, further comprising:

selecting a first tuner for a first received signal, wherein the step of selecting comprises the step of resolving conflicts relating to the selecting, wherein the first tuner comprises an available tuner on the network;

coupling the first tuner to the first storage medium;

allocating space on the first storage medium to record received signals; and

storing the first received signal on the first storage medium during a predetermined time.

19. (New) The method of claim 18, wherein the step of resolving conflicts to select an available tuner comprises the steps of:

determining whether the first tuner is available to receive a signal;

if so, selecting the first tuner to receive the signal;

if not, determining a second tuner that is potentially available for selection;

determining whether the second tuner has assigned clients;

if the second tuner has assigned clients, querying the clients assigned to the second tuner to determine whether the assigned clients permit reassignment of the second tuner; and

if reassignment is permitted, selecting the second tuner to receive the received signal,

if reassignment is not permitted, then searching for a third tuner available for selection on the network.

20. (New) The method of claim 17, further comprising:

selecting tuners located within the first PVR media server within the network, the first PVR media server comprising a plurality of tuners;

coupling a plurality of clients, by using the network, to the first PVR media server;

assigning at least a first client and a second client to at least a first tuner and a second tuner;

and

transferring, over the network, the buffered signals to the first and second clients.

21. (New) The method of claim 17, further comprising the step of selecting a plurality of tuners located in a plurality of PVR media servers distributed over the network.